ATLANTIC OCEAN PAINT
COLORS OF THE WORLD BROUGHT HOME

Material Safety Data Sheet *Waterbased*

Document # : MSD-03 / WB /0021
Version : 001
Issued Date : 10/10/2019

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION	
Product name	MARLIN EMULSION PAINT
Chemical description	Acrylic modified emulsion
Supplier	PT. ATLANTIC OCEAN PAINT Jalan Kepatihan Industri No.6, Desa Kepatihan, Kec. Menganti, Guntung, Kepatihan, Gresik, Kabupaten Gresik, Jawa Timur 61174
Emergency	Telp. 031 - 51203009 (hunting) 031-99008814
2. COMPOSITION / INFORMATION ON INGREDIENTS	
Composition	Polymer type acrylic modified
Water	30 %
3. HAZARD IDENTIFICATION	
Hazard Classification	Non Hazardous
Reactivity	Stable
Flammability	Unflammable
4. FIRST AID MEASURES	
General	In all cases of doubt or when symptoms persists seek medical advice immediately.
Inhalation	Move to fresh air
Skin contact	Remove immediately with plenty of water and soap.
Eye contact	Rinse for at least 15 minutes with plenty of water.
Ingestion	Give plenty of water to drink. Do not induce vomiting
5. FIRE FIGHTING MEASURES This product is a non flammable aqueous emulsion	
Extinguishing media to be avoided	None
Special fighting fire procedures	None
Special protective equipment for firefighters	Use self contained breathing apparatus when fighting fires in enclosed areas.

The information contained herein is to the best of our knowledge accurate and reliable. However, as use conditions are not within our control no guarantees are given or to be inferred nor is freedom from any patent to be inferred

6. HANDLING AND STORAGE	
Handling	Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do not breathe the vapors.
Storage	Keep container tightly closed in a dry and well ventilated place.
7. PERSONAL PROTECTION	
Respiratory protection	None should be required. If necessary, use OSHA/NIOSH approved respirators in poorly ventilated areas.
Hand protection	Use impervious gloves to water and soap
Eye protection	Safety goggles
Skin protection	Long sleeved clothing, a safety shower.
8. PHYSICAL PROPERTIES AND APPLICATION	
Physical state	White, Colours
Viscosity (Poise) ,32°C	15 – 17
Non Volatile (%)	60 ± 2
Coating method	Brush, roller or spray
Specific Gravity,32°C	1.57 ± 0.05
Flash point	NA(water solution)
Explosion limit	NA(water solution)
9. STABILITY AND REACTIVITY Stable under recommended storage and handling conditions.	

PT. Atlantic Ocean Paint
031-51203009 / 031- 99008814
info@atlanticoceanpaint.com
www.atlanticoceanpaint.com
atlanticoceanpaint

ISO 9001:2015 certified

Scan Me to view all AOP products

The information contained herein is to the best of our knowledge accurate and reliable. However, as use conditions are not within our control no guarantees are given or to be inferred nor is freedom from any patent to be inferred