

Material Safety Data Sheet Solventbased Document #: MSD-02 / SB / 0010

Version : 001 Issued Date: 10/10/2019

1. CHEMICAL PRODUCT AND	COMPANY IDENTIFICATION
Product name	NEPTUNE AUTOMOTIVE UNDERCOAT
Chemical description	Alkyd modified
Supplier	PT. ATLANTIC OCEAN PAINT Jalan Kepatihan Industri No.6, Desa Kepatihan, Kec. Menganti, Guntung, Kepatihan, Gresik, Kabupaten Gresik, Jawa Timur 61174
Emergency	Telp. 031 - 51203009 (hunting) 031-99008814
2. HAZARD IDENTIFICATION	The vapors are irritating to the eyes, the skin and the respiratory tract. Frequent or continuous skin contact causes irritation and may lead to dermatitis. The product is flammable.
3. PHYSICAL AND CHEMICAL F	PROPERTIES (* Derived from the solvents)
Physical state	Black
% Solids	69 - 71% W/W
Start boiling point	160°C *
Melting point	<-20°C
Relative density	1.02 kg/dm³
Vapor pressure	1 mbar (20°C) *
Vapor density	4.5 (air = 1) *
Solubility in water	Insoluble
PH	Not applicable
Flash point	42°C, Method Abel - Pensky, Closed cup
Auto ignition temperature	230°C*
4. FIRE FIGHTING MEASURES	
Extinguishing media	Foam, CO2 , and powder. Don't use water.
Special risk	Nitrous gasses are produced in case of fire.
Protective equipment	Apply self contained breathing apparatus.
5. FIRST AID MEASURES	
General	In all cases of doubt or when symptoms persists seek medical advice immediately.
Inhalation	Remove immediately to fresh air, avoid exertion
Skin contact	Wash immediately with plenty of water and soap. Remove contaminated clothing.
Eye contact	Rinse for at least 15 minutes with plenty of water.
Ingestion	Give plenty of water to drink. Do not induce vomiting.



Material Safety Data Sheet Solventbased Document #: MSD-02 / SB / 0010

Version : 001 Issued Date: 10/10/2019

6. HANDLING AND STORAGE	
Handling	 Apply proper ventilation, possibly combined with a local exhaust. Do not eat, smoke or drink during use. Use only explosion proof equipment. Avoid contact with strong oxidizers. Avoid contact with certain plastics like PVC and natural rubber, because these materials will dissolve.
Storage	 - Keep away from sources of ignition – no smoking. - Keep in original, well - closed packaging. - Store at a well ventilated place. - Comply with governmental regulations.
7. TOXICOLOGICAL INFORMATION	 No experimental data of the product available. Respiratory exposure to the vapors may lead to coughing, dizziness, sickness, drowsiness and vomiting. Long term exposure may lead to effects of the central nervous system. Frequent or continuous skin contact may lead to irritation and dermatitis
8. EXPOSURE CONTROLS / PERSONAL PROTECTIONS	
All III III III III III III III III III	
Respiratory protection	Install proper ventilations. If not feasible install proper ventilation, possibly combined with a local exhaust. Try to reach the lowest possible exposure.
Respiratory protection Hand protection	possibly combined with a local exhaust. Try to reach the lowest
	possibly combined with a local exhaust. Try to reach the lowest possible exposure.
Hand protection	possibly combined with a local exhaust. Try to reach the lowest possible exposure. Use proper gloves (neoprene or nitril rubber)
Hand protection Eye protection	possibly combined with a local exhaust. Try to reach the lowest possible exposure. Use proper gloves (neoprene or nitril rubber) Wear safety goggles against splashing

PT. Atlantic Ocean Paint 031-51203009 / 031- 99008814 info@atlanticoceanpaint.com www.atlanticoceanpaint.com (o) atlanticoceanpaint



