



ALTEX EMULSION PAINT

ALTEX EMULSION PAINT is a superior plastic emulsion paint based on a specially chosen acrylic modified binder. Formulated with non-fading pigment, this result in a high covering capacity coupled with outstanding hiding power.

TYPE	Acrylic modified emulsion
GLOSS	Matt finish
THEORITICAL COVERAGE	± 3 m ² /kg
VISCOSITY(POISE), 32°C	15 – 18
SPECIFIC GRAVITY, 32°C	1.50 ± 0.11
DRYING TIME	1 – 2 hours
THINNER	Clean water, approx. 20 - 30 %
METHOD OF APPLICATION	Brush, roller or spray
PRE-TREATMENT	<p>Cleaning</p> <ol style="list-style-type: none"> 1. New Surfaces must be cleaned from loose dirt and dust etc. <ul style="list-style-type: none"> * Minor cracks, holes, leakage and loose plaster must be repaired. * The new surfaces need minimal 21 days for normal drying. * Moisture < 6%, Alkali 6 – 10 * Then apply 1 – 2 coat of ALTEX NATURETONE PRIMER * Wall filler is suggested only for minor cracks. * Then apply 2 – 3 coats of ALTEX EMULSION. 2. Previously painted surfaces must be cleaned from dirt, dust, fungus algae and flaking old paint. <ul style="list-style-type: none"> * Moisture < 6%, Alkali 6 – 10 * Then apply 1 – 2 coat of ALTEX NATURETONE PRIMER * Wall filler is suggested only for minor cracks. * Then apply 2 – 3 coats of ALTEX EMULSION.
ATTENTION	The work should be carried out on dry surfaces.

PT. Atlantic Ocean Paint
031-51203009 / 031- 99008814
info@atlanticoceanpaint.com
www.atlanticoceanpaint.com
atlanticoceanpaint

