



ALTEX NATURETONE PRIMER

ALTEX NATURETONE PRIMER is a specially formulated wall primer to help prevent and protect against alkali for new cement plaster, concrete, asbestos cement where alkali usually exists. Also, for priming previously painted masonry surfaces.

TYPE	Acrylic modified emulsion
GLOSS	Matt finish
THEORITICAL COVERAGE	± 4 m ² /liter (depends on the surface)
VISCOSITY(POISE), 32°C	10 – 11
SPECIFIC GRAVITY, 32°C	1.35 ± 0.02
DRYING TIME	1 – 2 hours
THINNER	Clean water, approx. 15% - 25%
METHOD OF APPLICATION	Brush, roller or spray
PRE-TREATMENT	<p>Cleaning</p> <ol style="list-style-type: none"> 1. New Surfaces must be cleaned from loose dirt and dust etc. <ul style="list-style-type: none"> * Minor cracks, holes, leakage and loose plaster must be repaired. * The new surfaces need minimal 21 days for normal drying. * Moisture < 6%, Alkali 6 – 10 * Then apply 1 – 2 coat of ALTEX NATURETONE PRIMER * Wall filler is suggested only for minor cracks. 2. Previously painted surfaces must be cleaned from dirt, dust, fungus algae and flaking old paint. <ul style="list-style-type: none"> * Moisture < 6%, Alkali 6 – 10 * Then apply 1 – 2 coat of ALTEX NATURETONE PRIMER * Wall filler is suggested only for minor cracks.
ATTENTION	The work should be carried out on dry surfaces.

PT. Atlantic Ocean Paint
031-51203009 / 031- 99008814
info@atlanticoceanpaint.com
www.atlanticoceanpaint.com
atlanticoceanpaint

