



ALTEX NATURETONE EXTERIOR & INTERIOR EMULSION PAINT

ALTEX NATURETONE EXTERIOR & INTERIOR EMULSION PAINT is a premium quality, modified acrylic emulsion paint that endures and washable. Recommended for exterior as well as interior use with anti fungus, algae and mold properties.

TYPE	Acrylic modified emulsion
GLOSS	Matt finish
THEORITICAL COVERAGE	± 3 - 4 m ² /kg
VISCOSITY(POISE), 32°C	15 - 20
SPECIFIC GRAVITY, 32°C	1.47 ± 0.11
DRYING TIME	1 - 2 hours
THINNER	Clean water, approx. 20% - 30 %
METHOD OF APPLICATION	Brush, roller or spray
PRE-TREATMENT	<p>Cleaning</p> <ol style="list-style-type: none"> New Surfaces must be cleaned from loose dirt and dust etc. <ul style="list-style-type: none"> * Minor cracks, holes, leakage and loose plaster must be repaired. * The new surfaces need minimal 21 days for normal drying. * Moisture < 6%, Alkali 6 - 10 * Then apply 1 - 2 coat of ALTEX NATURETONE PRIMER * Wall filler is suggested only for minor cracks. * Then apply 2 - 3 coats of ALTEX NATURETONE. Previously painted surfaces must be cleaned from dirt, dust, fungus algae and flaking old paint. <ul style="list-style-type: none"> * Moisture < 6%, Alkali 6 - 10 * Then apply 1 - 2 coat of ALTEX NATURETONE PRIMER * Wall filler is suggested only for minor cracks. * Then apply 2 - 3 coats of ALTEX NATURETONE.
ATTENTION	The work should be carried out on dry surfaces.

PT. Atlantic Ocean Paint
031-51203009 / 031- 99008814
info@atlanticoceanpaint.com
www.atlanticoceanpaint.com
atlanticoceanpaint

