



FUKUDA EMULSION PAINT

FUKUDA EMULSION PAINT is designed for economical purposes. It is a high quality paint for a very low cost.

TYPE	Acrylic modified emulsion
GLOSS	Matt finish
THEORITICAL COVERAGE	± 2 m ² /kg
VISCOSITY (POISE), 32° C	15 – 16
SPECIFIC GRAVITY, 32° C	1.64 ± 0.03
DRYING TIME	1 – 2 hours
THINNER	Clean water, approx. 20 - 30 %
METHOD OF APPLICATION	Brush, roller or spray
PRE-TREATMENT	<p>Cleaning</p> <p>*New Surfaces must be cleaned from loose dirt and dust etc.</p> <ul style="list-style-type: none"> -Cracks, holes, leakage and loose plaster must be repaired. -The new surfaces need minimal 21 days for normal drying. -Moisture <6%, Alkali 6 - 10 -Wall filler is suggested only for minor cracks. -Then apply 2 – 3 coats of FUKUDA EMULSION. <p>*Previously painted surfaces must be cleaned from dirt, dust, fungus algae and flaking old paint.</p> <ul style="list-style-type: none"> -Moisture <6%, Alkali 6 - 10 -Wall filler is suggested only for minor cracks. -Then apply 2 – 3 coats of FUKUDA EMULSION.
ATTENTION	The work should be carried out on dry surfaces.

PT. Atlantic Ocean Paint
 031-51203009 / 031- 99008814
 info@atlanticoceanpaint.com
 www.atlanticoceanpaint.com
 atlanticoceanpaint

