



JAVA EXTERIOR DIRTPROOF EMULSION PAINT

JAVA EXTERIOR DIRTPROOF EMULSION PAINT is a high quality satin finish 100% full acrylic water-based paint that endures and is washable. It is made from a special formulation of non-fading pigment with anti fungus, algae and mold properties, which result in a highly durable weather resistant exterior wall paint.

TYPE	100% Full acrylic emulsion
GLOSS	Satin Finish
THEORITICAL COVERAGE	± 5 m ² /liter
VISCOSITY(POISE), 32°C	9 – 10
SPECIFIC GRAVITY, 32°C	1.24 ± 0.1
DRYING TIME	1 – 2 hours
THINNER	Clean water, approx. 10% - 25%
METHOD OF APPLICATION	Brush, roller or spray
PRE-TREATMENT	<p>Cleaning</p> <ol style="list-style-type: none"> New Surfaces must be cleaned from loose dirt and dust etc. <ul style="list-style-type: none"> * Minor cracks, holes, leakage and loose plaster must be repaired. * The new surfaces need minimal 21 days for normal drying. * Moisture < 6%, Alkali 6 - 10 * Then apply 1-2 coat of JAVA PRIMER * Wall filler is suggested only for minor cracks. * Then apply 2 – 3 coats of JAVA EXTERIOR. Previously painted surfaces must be cleaned from dirt, dust, fungus algae and flaking old paint. <ul style="list-style-type: none"> * Moisture < 6%, Alkali 6 - 10 * Then apply 1-2 coat of JAVA PRIMER * Wall filler is suggested only for minor cracks. * Then apply 2 – 3 coats of JAVA EXTERIOR.
ATTENTION	The work should be carried out on dry surfaces.

PT. Atlantic Ocean Paint
031-51203009 / 031- 99008814
info@atlanticoceanpaint.com
www.atlanticoceanpaint.com
atlanticoceanpaint

