



JAVA PRIMER

JAVA PRIMER is a specially formulated high quality wall primer which is resistant to attack by alkali. It provides a protective layer for subsequent coats of paint and improves their adhesion.

TYPE	Acrylic modified emulsion
COLOR	White
THEORITICAL COVERAGE	± 5 m ² /liter
VISCOSITY(POISE), 32°C	9 – 10
SPECIFIC GRAVITY, 32°C	1.31 ± 0.02
DRYING TIME	1 – 2 hours
THINNER	Clean water, approx. 10% - 15%
METHOD OF APPLICATION	Brush, roller or spray
PRE-TREATMENT	<p>Cleaning</p> <ol style="list-style-type: none"> New Surfaces must be cleaned from loose dirt and dust etc. <ul style="list-style-type: none"> * Minor cracks, holes, leakage and loose plaster must be repaired. * The new surfaces need minimal 21 days for normal drying. * Moisture < 6%, Alkali 6 – 10 * Then apply 1 – 2 coat of JAVA PRIMER * Wall filler is suggested only for smooth cracks. Previously painted surfaces must be cleaned from dirt, dust, fungus algae and flaking old paint. <ul style="list-style-type: none"> * Moisture < 6%, Alkali 6 - 10 * Then apply 1 – 2 coat of JAVA PRIMER * Wall filler is suggested only for smooth cracks.
ATTENTION	The work should be carried out on dry surfaces.

PT. Atlantic Ocean Paint
031-51203009 / 031- 99008814
info@atlanticoceanpaint.com
www.atlanticoceanpaint.com
@atlanticoceanpaint

