

Technical Data Sheet Waterbased

Document #: TDS-03 / WB / 0002

Version : 001 Issued Date : 10/10/2019



JAVA SUPERINTERIOR EMULSION PAINT

JAVA SUPERINTERIOR EMULSION PAINT is a high quality satin finish modified acrylic water based paint that endures and is washable. It is especially made for insulation purposes, containing non-fading pigments with anti fungus, algae and mold properties which result in a highly durable weather resistant interior wall paint.

TYPE	Acrylic modified emulsion
GLOSS	Egg Shell
THEORITICAL COVERAGE	± 5 m²/liter
VISCOSITY(POISE), 32°C	9 – 10
SPECIFIC GRAVITY, 32°C	1.33 ± 0.18
DRYING TIME	1 – 2 hours
THINNER	Clean water, approx. 10% - 25%
METHOD OF APPLICATION	Brush, roller or spray
PRE-TREATMENT	Cleaning 1. New Surfaces must be cleaned from loose dirt and dust etc. * Minor cracks, holes, leakage and loose plaster must be repaired. * The new surfaces need minimal 21 days for normal drying. * Moisture < 6%, Alkali 6 – 10 * Then apply 1 – 2 coat of JAVA PRIMER * Wall filler is suggested only for minor cracks. * Then apply 2 – 3 coats of JAVA SUPERINTERIOR. 2. Previously painted surfaces must be cleaned from dirt, dust,
	fungus algae and flaking old paint. * Moisture < 6%, Alkali 6 – 10 * Then apply 1 – 2 coat of JAVA PRIMER * Wall filler is suggested only for minor cracks. * Then apply 2 – 3 coats of JAVA SUPERINTERIOR
ATTENTION	The work should be carried out on dry surfaces.

PT. Atlantic Ocean Paint 031-51203009 / 031- 99008814 info@atlanticoceanpaint.com www.atlanticoceanpaint.com



