ATLANTIC OCEAN PAINT
COLORS OF THE WORLD BROUGHT HOME

Technical Data Sheet *Waterbased*

Document # : TDS-03 / WB / 0021
Version : 001
Issued Date : 10/10/2019

# MARLIN EMULSION PAINT

MARLIN EMULSION PAINT is designed for economical purposes. It is a high quality paint for a very low cost.

| | |
|---|---|
| TYPE | Acrylic modified emulsion |
| GLOSS | Matt finish |
| THEORITICAL COVERAGE | ± 2 $m^2$/kg |
| VISCOSITY (POISE), 32° C | 15 – 17 |
| SPECIFIC GRAVITY, 32° C | 1.57 ± 0.05 |
| DRYING TIME | 1 – 2 hours |
| THINNER | Clean water, approx. 20 - 30 % |
| METHOD OF APPLICATION | Brush, roller or spray |
| PRETREATMENT | Cleaning<br>*New Surfaces must be cleaned from loose dirt and dust etc.<br>-Minor cracks, holes, leakage and loose plaster must be repaired.<br>-The new surfaces need minimal 21 days for normal drying.<br>-Moisture <6%, Alkali 6 - 10<br>-Wall filler is suggested only for smooth cracks.<br>-Then apply 2 – 3 coats of MARLIN EMULSION.<br>*Previously painted surfaces must be cleaned from dirt, dust, fungus algae and flaking old paint.<br>-Moisture <6%, Alkali 6 - 10<br>-Wall filler is suggested only for smooth cracks.<br>-Then apply 2 – 3 coats of MARLIN EMULSION. |
| ATTENTION | The work should be carried out on dry surfaces. |

PT. Atlantic Ocean Paint
031-51203009 / 031- 99008814
info@atlanticoceanpaint.com
www.atlanticoceanpaint.com
atlanticoceanpaint

ISO 9001:2015 certified

Scan Me to view all AOP products

The information contained herein is to the best of our knowledge accurate and reliable. However, as use conditions are not within our control no guarantees are given or to be inferred nor is freedom from any patent to be inferred