



KUNCI MAS PLAMIR

KUNCI MAS PLAMIR is based on a acrylic modified emulsion. Easy sandability permits a smooth coat of emulsion paint. It is further characterized by its easy a application and clean up ability. It is suggested only for filling minor cracks.

TYPE	Acrylic modified emulsion
COLOR	White
GLOSS	Matt finish
SPREADING RATE	± 2 - 3 m ² /kg (depends on the surface)
VISCOSITY (POISE), 32° C	38 – 39
SPECIFIC GRAVITY, 32° C	1.64 ± 0.02
DRYING TIME	1 – 2 hours
THINNER	Clean water
METHOD OF APPLICATION	Putty knife
PRE-TREATMENT	<p>Cleaning</p> <p>*New Surfaces must be cleaned from loose dirt and dust etc. -Cracks, holes, leakage and loose plaster must be repaired. -The new surfaces need minimal 21 days for normal drying. -Moisture <6%, Alkali 6 - 10 -Then apply KUNCI MAS PLAMIR -Plamir is suggested only for minor cracks.</p> <p>*Previously painted surfaces must be cleaned from dirt, dust, fungus algae and flaking old paint. -Moisture <6%, Alkali 6 - 10 -Then apply KUNCI MAS PLAMIR if needed -Plamir is suggested only for minor cracks.</p>
ATTENTION	: The work should be carried out on dry surfaces.

PT. Atlantic Ocean Paint
031-51203009 / 031- 99008814
info@atlanticoceanpaint.com
www.atlanticoceanpaint.com
@ atlanticoceanpaint

