



## SAHARA PLAMIR

SAHARA PLAMIR is based on a acrylic modified emulsion. Application is simple. When sanded a completely smooth surface is obtained.

TYPE	Acrylic modified emulsion
COLOR	White
GLOSS	Matt finish
SPREADING RATE	± 2 – 3 m <sup>2</sup> /kg (depends on the surface)
VISCOSITY (POISE), 32° C	30 – 35
SPECIFIC GRAVITY, 32° C	1.54 ± 0.02
DRYING TIME	1 – 2 hours
THINNER	Clean water
METHOD OF APPLICATION	Putty knife
PRE-TREATMENT	<p>Cleaning</p> <p>*New Surfaces must be cleaned from loose dirt and dust etc.</p> <ul style="list-style-type: none"> <li>-Cracks, holes, leakage and loose plaster must be repaired.</li> <li>-The new surfaces need minimal 21 days for normal drying.</li> <li>-Moisture &lt;6%, Alkali 6 - 10</li> <li>-Then apply SAHARA PLAMIR</li> <li>-Plamir is suggested only for minor cracks.</li> </ul> <p>*Previously painted surfaces must be cleaned from dirt, dust, fungus algae and flaking old paint.</p> <ul style="list-style-type: none"> <li>-Moisture &lt;6%, Alkali 6 - 10</li> <li>-Then apply SAHARA PLAMIR if needed</li> <li>-Plamir is suggested only for minor cracks.</li> </ul>
ATTENTION	: The work should be carried out on dry surfaces.

PT. Atlantic Ocean Paint  
031-51203009 / 031- 9908814  
info@atlanticoceanpaint.com  
www.atlanticoceanpaint.com  
@atlanticoceanpaint

